

**Floorstanding WC rimless combination with cistern  
with fixing holes for floor fixation**

**82715.2**



**TECHNICAL DATA**

Order no.	82715.2
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 782 2 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 783
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	33,0 kg
Accessories excl.	Seat and cover, order no. 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89115.1
Mounting acc. incl.	Fastening kit, order no. 89175.7

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm  
outlet horizontal, VARIO vertical 70 - 250 mm  
back to wall, concealed fixation, 2 fixing holes  
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked  
Further options / accessories: Surface refinement LCC, with shut-off valve option 783, WC seat and cover, 89115.0, 89115.2, WC seat and cover with automatic lowering 89115.1  
Order no. 82715.2

**TECHNICAL DRAWINGS / S 1 : 20**

