

## Floorstanding WC rimless combination with cistern without fixing holes for floor fixation 82715.3



### TECHNICAL DATA

Order no.	82715.3
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 782 with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 783
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	33,0 kg
Accessories excl.	Seat and cover, order no. 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89115.1

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

### SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm  
outlet horizontal, VARIO vertical 70 - 250 mm, back to wall  
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked  
Further options / accessories: Surface refinement LCC, with shut-off valve option 783, WC seat and cover, 89115.0, 89115.2, WC seat and cover with automatic lowering 89115.1  
Order no. 82715.3

### TECHNICAL DRAWINGS / S 1 : 20

